
























→ IDEAL HIGH-CAPACITY SHREDDERS AT A GLANCE

DESCRIPTION / MODEL	CATEGORY HIGH-CAPACITY SHREDDERS					
	→ IDEAL 4605		→ IDEAL 4107		→ IDEAL 5009-2-C/C	
	→ IDEAL 4605-C/C		→ IDEAL 4107-C/C			
	4605	-C/C	-C/C	4107	-C/C	5009-2-C/C
Shred width, mm	6	4 x 60	2 x 15	6	6 x 50	8 x 40-80
Performance in sheets, A4 paper 70 g/m ²	90-100	65-70	35-40	90-110	80-90	600-700
Performance in sheets, A4 paper 80 g/m ²	75-85	55-60	29-34	75-95	68-78	500-600
Security level (DIN 32 757 standard)	2	3	4	2	3	2
Paper clip proof cutting head						
Cutting head shreds plastic cards						 suitable for complete lever arch files
Cutting head shreds CDs and DVDs						-
Cutting head shreds diskettes (3.5 inches)						
Centralised oiler	-	-	-	•	•	•
Feed opening, mm	460			410		500
Shred speed, m/sec.	0.20			0.30	0.26	0.23 / 0.12 ²
Capacity for shreds, litres	230			300		300
Power connection, volts / Hz (three phase) ¹	400 / 50 / 3~			400 / 50 / 3~		400 / 50 / 3~
Motor capacity, kW	2.2			4.0	3.0	9.0 (2 x 4.5)
Automatic start/stop via photo cell	•			-		-
Push buttons for forward/stop/reverse	•			•		•
Automatic reverse / automatic power cut-off in case of paper jam	• / •			- / •		• / •
Automatic cut-off if shred bin is full	•			•		•
Electric door protection	•			•		•
Thermal overload switch	•			•		•
Movable on castors	•			•		•
Dimensions, mm (H x W x D)	1700 x 740 x 765			1440 x 1240/690 ³ x 1700		1714 x 1036 x 2170/3070 ⁴
Weight, kg	256	256	256	350	350	1130
Prices for machines						
Prices for accessories	PAPERBOX "Collect & Shred"					
	Modular conveyor belt system					
	Second shred trolley					

¹ other voltages available

² variable shred speed »2-MATIC«

³ transportation width (without side tables)

⁴ depth with conveyor belt system



→ IDEAL 4605

→ IDEAL 4605-C/C

→ IDEAL 4107

→ IDEAL 4107-C/C

→ IDEAL 5009-2-C/C