

# IDEAL BUSINESS SHREDDERS AT A GLANCE

DESCRIPTION / MODEL	CATEGORY DESKTOP DOCUMENT SHREDDERS															
	→ IDEAL 2220	→ IDEAL 2240		→ IDEAL 2260		→ IDEAL 2360				→ IDEAL 2403			→ IDEAL 2404			→ AL1
		→ IDEAL 2240-C/C		→ IDEAL 2260-C/C		→ IDEAL 2360-C/C				→ IDEAL 2403-C/C			→ IDEAL 2404-C/C			
						→ IDEAL 2360-SM/C										
	2220	2240	-C/C	2260	-C/C	2360	-C/C	-C/C	-SM/C	2403	-C/C	-C/C	2404	-C/C	-C/C	AL1
Shred width, mm	4	4	3 x 25	4	3 x 25	4	4 x 40	2 x 15	0,8 x 5	4	4 x 40	2 x 15	4	4 x 40	2 x 15	2 x 15
Performance in sheets, A4 paper 70 g/m <sup>2</sup>	11-13	11-13	6-7	11-13	6-7	15-17	13-15	10-12	4-5	22-24	16-18	11-13	22-24	16-18	11-13	11-13
Performance in sheets, A4 paper 80 g/m <sup>2</sup>	9-11	9-11	5-6	9-11	5-6	12-14	11-13	8-10	3-4	19-21	13-15	9-11	19-21	13-15	9-11	9-11
Security level (DIN 32 757 standard)	2	2	3	2	3	2	3	4	Level 6	2	3	4	2	3	4	4
Paper clip proof cutting head	✂	✂	✂	✂	✂	✂	✂	✂	-	✂	✂	✂	✂	✂	✂	✂
Cutting head shreds plastic cards	☐	☐	-	☐	-	☐	☐	☐	-	☐	☐	☐	☐	☐	☐	☐
Cutting head shreds CDs and DVDs   diskettes (3.5 inches)	-	-	-	-	-	-	-	-	-	Ⓢ	Ⓢ	-	Ⓢ	Ⓢ	-	-
Automatic oil injection on the cutting shafts during shredding operation	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Feed opening, mm	220	220		220		240				240			240			240
Shred speed, m/sec.	0.06	0.06		0.06		0.10	0.05	0.05	0.05	0.10			0.10			0.10
Shred collection in	shred bin	shred bin		shred bin		permanent plastic bag				permanent plastic bag			permanent plastic bag			shred bin
Capacity for shreds, litres	20	20		20		35				35			50			25
Power connection, volts / Hz (single phase) <sup>1</sup>	230 / 50 / 1~	230 / 50 / 1~		230 / 50 / 1~		230 / 50 / 1~				230 / 50 / 1~			230 / 50 / 1~			230 / 50 / 1~
Motor capacity, W	150	150		150		390				580			580			580
Automatic start/stop via photo cell	-	•		•		•				•			•			•
ECC Electronic Capacity Control – indication of the used sheet capacity	-	-		-		-				-			-			-
SPS Safety Protection System:	-	-		-		•				•			•			•
- Safety flap in the feed opening <sup>2</sup>	• (mechanically)	• (mechanically)		• (mechanically)		• (electronically controlled)				• (electronically controlled)			• (electronically controlled)			• (electronically controlled)
- Multifunction element EASY_SWITCH <sup>2</sup>	-	-		-		•				•			•			•
- Automatic reverse / automatic power cut-off <sup>2</sup>	-	-		-		• / •				• / •			• / •			• / •
- Automatic cut-off if shred bag is full <sup>2</sup>	-	-		-		•				•			•			•
- Electronic door protection via a magnetic proximity switch <sup>2</sup>	-	automatic cut-off if the shredder unit is removed from the bin		automatic cut-off if the shred bin is removed from the cabinet		•				•			•			•
- Double motor protection against overheating <sup>2</sup>	•	•		•		•				•			•			•
- Energy saving mode <sup>2</sup>	-	-		-		•				•			•			•
Dimensions, mm (H x W x D)	452 x 345 x 215	452 x 345 x 215		537 x 345 x 220		630 x 395 x 295				630 x 395 x 295			730 x 395 x 295			600 x 410 x 240
Weight, kg	6	6	7	10.5	11.5	19.5	20	20	20	21	21.5	21.5	22.5	23	23	21
Prices for machines																

<sup>1</sup> other voltages available

<sup>2</sup> element of the SPS safety package (Safety Protection System)

<sup>3</sup> plastic bag suspension with pull-out mechanism on wheels for easy removal of the full bag



→ IDEAL 2220      → IDEAL 2240      → IDEAL 2260      → IDEAL 2360      → IDEAL 2403      → IDEAL 2404      → AL1  
 → IDEAL 2240-C/C      → IDEAL 2260-C/C      → IDEAL 2360-C/C      → IDEAL 2403-C/C      → IDEAL 2404-C/C  
 → IDEAL 2360-SM/C